




SNR Bearing Argentina



308 Bearing 2D drawings and 3D CAD models

40 mm x 90 mm x 23 mm skf 308 Deep groove ball bearings

Bearing No. 308

| | |
|---|--------------------------|
| Size | 90x40x23 mm |
| Bore Diameter | 90 mm |
| Outer Diameter | 40 mm |
| Width | 23 mm |
| d | 40 mm |
| D | 90 mm |
| B | 23 mm |
| d ₁ | 56.11 mm |
| D ₂ | 77.7 mm |
| r _{1,2} - min. | 1.5 mm |
| d _a - min. | 49 mm |
| D _a - max. | 81 mm |
| r _a - max. | 1.5 mm |
| Basic dynamic load rating - C | 45.7 kN |
| Basic static load rating - C ₀ | 36 kN |
| Fatigue load limit - P _u | 1.5 kN |
| Reference speed | 14000 r/min |
| Limiting speed | 8500 r/min |
| Calculation factor - k _r | 0.05 |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.65 |



SNR Bearing Argentina

| | |
|---------------------------------|---|
| EAN | 7316577003966 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | Yes |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 40MM Bore; 90MM Outside Diameter; 23MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; Yes Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 308 |
| Weight / LBS | 1.42 |
| Outside Diameter | 3.543 Inch 90 Millimeter |
| Outer Race Width | 0.906 Inch 23 Millimeter |
| Bore | 1.575 Inch 40 Millimeter |
| bore diameter: | 40 mm |
| static load capacity: | 36 kN |
| outside diameter: | 90 mm |
| precision rating: | ABEC 3 (ISO Class 6) |
| | |



SNR Bearing Argentina

| | |
|--------------------------------|---|
| overall width: | 23 mm |
| finish/coating: | Uncoated |
| bore type: | Round |
| cage material: | Steel |
| closure type: | Open |
| outer ring width: | 23 mm |
| row type & fill slot: | Single Row Filling Slot |
| fillet radius: | 1.5 mm |
| snap ring included: | Without Snap Ring |
| maximum rpm: | 8500 RPM |
| internal clearance: | C0 |
| series: | 30 |
| dynamic load capacity: | 45.7 kN |
| thrust application warning: | This product can not be used in Thrust Applications |
| d_1 | 56.11 mm |
| D_2 | 77.7 mm |
| $r_{1,2}$ min. | 1.5 mm |
| d_a min. | 49 mm |
| D_a max. | 81 mm |
| r_a max. | 1.5 mm |
| Basic dynamic load rating C | 45.7 kN |
| Basic static load rating C_0 | 36 kN |
| Fatigue load limit P_u | 1.53 kN |
| Calculation factor k_r | 0.05 |
| Mass bearing | 0.64 kg |