



# SNR Bearing Argentina



## 50 mm x 90 mm x 20 mm skf 210-Z Deep groove ball bearings

Bearing No. 210-Z

210-Z Bearing 2D drawings and 3D CAD models

Size	50x90x20 mm
Bore Diameter	50 mm
Outer Diameter	90 mm
Width	20 mm
d	50 mm
D	90 mm
B	20 mm
C	20 mm
d1	62,5 mm
r1 min.	1,1 mm
r2 min.	1,1 mm
D2	81,7 mm
da min.	57 mm
da max	62,4 mm
Da max.	83 mm
ra max.	1 mm
Weight	0,5 Kg
Basic dynamic load rating (C)	39,1 kN
Basic static load rating (C0)	34,5 kN
Fatigue load limit (Pu)	1,46
Reference speed	13000 r/min
Limiting speed	8000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF



## SNR Bearing Argentina

Minimum Buy Quantity	N/A
Weight / Kilogram	0.522
EAN	7316576679735
Product Group	B00308
Enclosure	1 Metal Shield
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	Yes
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	50MM Bore; 90MM Outside Diameter; 20MM Outer Race Diameter; 1 Metal Shield; Ball Bearing; ABEC 1   ISO P0; Yes Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	210 Z
Weight / LBS	1.1
Outer Race Width	0.787 Inch   20 Millimeter
Outside Diameter	3.543 Inch   90 Millimeter
Bore	1.969 Inch   50 Millimeter
bore diameter:	50 mm
static load capacity:	34.5 kN



## SNR Bearing Argentina

outside diameter:	90 mm
precision rating:	ABEC 3 (ISO Class 6)
overall width:	20 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Single Shield
outer ring width:	20 mm
row type & fill slot:	Single Row Filling Slot
fillet radius:	1 mm
snap ring included:	Without Snap Ring
maximum rpm:	8000 RPM
internal clearance:	C0
series:	21
dynamic load capacity:	39.1 kN
thrust application warning:	This product can not be used in Thrust Applications
$d_1$	62.51 mm
$D_2$	81.61 mm
$r_{1,2}$ min.	1.1 mm
$d_a$ min.	57 mm
$d_a$ max.	62.4 mm
$D_a$ max.	83 mm
$r_a$ max.	1 mm
Basic dynamic load rating C	39.1 kN
Basic static load rating $C_0$	34.5 kN
Fatigue load limit $P_u$	1.46 kN
Calculation factor $k_r$	0.04
Mass bearing	0.5 kg